

# AUXILIARY RELAY



## FEATURES

- \* *Polarised Coil with diode suppression*
- \* *2 sets of CHO contacts*
- \* *In and output coil terminals*
- \* *Standard 1 Gang plate mounted*
- \* *Surface or Flush Versions*
- \* *Front LED for relay operation*
- \* *Various Coil Voltages*

## GENERAL DESCRIPTION

A general purpose relay suitable for a number of applications including Fire Alarm Systems. The relay is mounted on a 1 gang plate suitable for fixing onto a standard back box of at least 25mm deep. The relay has two sets of CHO contacts rated at 5 amps. The coil is both polarised and diode suppressed. Coil terminals are proved for both Input & outputs to enable inline Connections. A LED provides indication that the relay has operated.

## TECHNICAL SPECIFICATION

Nominal Coil Voltage	——	24V DC or 12V dc (other coil voltages to order)
Coil Power Consumption	——	24v DC : 17mA
	——	12v DC : 33mA
Contacts	——	2 sets CHO : 5 amp @ 230v AC
Plate Material	——	ABS Plastic—White finish
Enclosure Size	——	125mm (W) x 105mm (H) x 45mm (D)

## ORDER CODES DETAILS

AR1/24/F - 24V DC coil Flush Mounting

AR1/24/S - 24V DC coil Surface Mounted

AR1/12/F - 12V DC coil Flush Mounting

AR1/12/S - 12V DC coil Surface Mounted

Contacts sales for other coil voltages

**ALARMTRONIC LTD**

Unit 14, Meridian Centre, Vulcan Way,  
Croydon, Surrey, CR0 9UG.

Tel : 01689 847626 Email : sales@alarmtronic.co.uk

Web: www.alarmtronic.co.uk