AUDIO / VISUAL UNITS

PULSING AUDIO / VISUAL UNIT



ORDER CODE DETAILS

FAV/ BM/ F

FAV/ BM/ S

GENERAL DESCRIPTION

An audio/visual unit suitable for use in public entertaining areas as Staff alarms. The unit is mounted on a 2 gang plate for fixing to a Back box of at least 25 mm deep . The LED's can be made to pulse in a number of ways (via jumper links) and the buzzer can be continuous or pulsing together with volume adjustment (via jumper links) . The buzzer can also be muted . Non standard materials and finishes are available to special order.

TECHNICAL SPECIFIC	ATION	
Nominal Voltage Input		24v DC (polarised)
Current consumption		25 mA @ 24v DC
Sound Output		80 db
Plate material		18 gauge metal finished White
Plate size		146 mm (w) x 86 mm (h) with fixings
		For standard double gang back box

AVAILABLE OPTIONS

- Non buzzer muted Version
- * Stainless Steel & Brass finishes

LOW CURRENT AUDIO / VISUAL UNIT

- with surface back box

- flush fitting



ORDER CODE DETAILS LCAV / F - flush fitting LCAV / S

- with surface back box

GENERAL DESCRIPTION

A low current audio/visual unit suitable for use as Bed - head or local Staff alarms. The unit is mounted on a 1 gang plate for fixing to a Back box of at least 25 mm deep . The LED is a large Red High Intensity type with a wide viewing angle . The unit is polarised and ideal for connecting to sounder circuits . Terminals are provided for Both input/output cables .

TECHNICAL SPECIFIC	ATION	
Nominal Voltage Input		24v DC (polarised)
Current consumption		10 mA
Sound Output		70 db
Led output / angle		Typically 13 mcd / 120 degrees
Plate material		ABS Plastic finished White
Plate size		86 mm (w) x 86 mm (h) with fixings
		For standard single gang back box

AVAILABLE OPTIONS

Stainless Steel & Brass finishes

Unit 14, Meridian Centre, Vulcan Way, Croydon, Surrey, CR0 9UG Tel : 01689 847626 Fax : 01689 841138 Email : sales@alarmtronic.co.uk Web : www.alarmtronic.co.uk