

# REMOTE INDICATORS

## SMOKE DETECTOR OPERATED - SQUARE



### GENERAL DESCRIPTION

A Smoke detector operated indicator with a 5 mm Red high intensity LED mounted on a 1 gang plate suitable for fixing to a back box of at least 16 mm depth . Designed for use with either conventional or addressable detectors thus eliminating the need to stock two types of indicators . The indicator is also polarised and therefore can be connected to a sounder output if required .

### TECHNICAL SPECIFICATION

Current—Conventional	—	12 mA @ 24v DC
Current - Addressable	—	25 mA Max
Typical lum. intensity	—	10 mcd
View angle	—	45 degrees
Plate material	—	ABS Plastic finished White
Plate size	—	86 mm ( w ) x 86 mm ( h ) with fixings For standard single gang back box

### ORDER CODE DETAILS

SRL/F - Flush fitting  
SRL/S - with surface back box

### AVAILABLE OPTIONS

- \* Stainless steel & Brass finishes
- \* Special legends
- \* Company Name & Logo ( minimum quantity requirement )

## SMOKE DETECTOR OPERATED - ROUND



### GENERAL DESCRIPTION

A Smoke detector operated indicator with a 5 mm Red high intensity LED mounted on a round plate suitable for ceiling fixing . Designed for use with either conventional or addressable detectors thus eliminating the need to stock two types of indicators . Suitable back boxes will have 50.80 mm fixing centres .

### TECHNICAL SPECIFICATION

Current - Conventional	—	12 mA @ 24v DC
Current - Addressable	—	25 mA Max
Typical lum. intensity	—	10 mcd
View angle	—	45 degrees
Plate material	—	18 gauge Sheet steel finished White
Plate size	—	85 mm diameter with fixings for standard box with 50.80 mm centres

### ORDER CODE DETAILS

RRL/F - Flush fitting

### AVAILABLE OPTIONS

- \* Stainless Steel & Brass finishes
- \* Company Name & Logo ( minimum quantity requirement )

**ALARMTRONIC LTD**

Unit 14 , Meridian Centre , Vulcan Way ,  
Croydon , Surrey , CR0 9UG  
Tel : 01689 847626 Fax : 01689 841138  
Email : sales@alarmtronic.co.uk  
Web : www.alarmtronic.co.uk