

## BOXED RELAY UNIT TYPE—RU1 & 2



### FEATURES

- \* *Polarised Coil with diode suppression*
- \* *2 sets of CHO contacts*
- \* *In and output coil terminals*
- \* *Sheet steel box construction with 20mm Knockout Top & Bottom*
- \* *Internal LED for relay operation*
- \* *Various Coil Voltages*

### GENERAL DESCRIPTION

A range of boxed relays housed in a Sheet steel metal enclosure with entry knockouts located in both Top & bottom of the enclosure together with internal wall fixings. Each relay has two sets of CHO contacts either rated at 5 amp or 10 amp. The coil is both polarised and diode suppressed. Coil terminals are proved for both Input and Outputs to enable inline Connections. A internal LED provides indication that the relay has operated .

### TECHNICAL SPECIFICATION

Nominal Coil Voltage	—	24V DC or 12VDC (other coil voltages to order)
Coil Power Consumption	—	24V DC : 17mA (5 amp contacts) : 33mA (10 Amp contacts)
	—	12V DC : 33mA (5 amp contacts) : 66mA (10 Amp contacts)
Contacts	—	2 sets CHO : 5 or 10 amp maximum @ 230v AC
Enclosure Construction	—	Sheet steel with screw lid , 4 knockouts Top & bottom finished Grey White to RAL 9002
Enclosure Size	—	125mm (W) x 105mm (H) x 45mm (D)

### ORDER CODES DETAILS

**RU1/24 - 5 Amp contacts, 24V DC coil**

**RU1/12 - 5 Amp contacts, 12V DC coil**

**RU2/24 - 10 Amp contacts, 24V DC coil**

**RU2/12 - 10 Amp contacts, 12V DC coil**

Contacts sales for other coil voltages

**ALARMTRONIC LTD**

Unit 14, Meridian Centre, Vulcan Way,  
Croydon, Surrey, CR0 9UG.

Tel : 01689 847626 Email : sales@alarmtronic.co.uk

Web: www.alarmtronic.co.uk